



(715) 838-8964 | (877) 838-4800
www.airtitewindowsystems.com

Features of Vinyl-Pro Windows from Air-Tite Window Systems:

- Easy clips or slides to release the sash from the frame for easy cleaning. (Double-Hung)
- Seals and weather strips around glass and sashes to help insulate
- Moisture absorbing agent to prevent fogging between panes of glass
- Aluminum supports in the horizontal sash parts for extra strength and load distribution. (Double-hung)
- Two stops that the sashes fit into, instead of just one, ensuring a tight fit. (Double-hung)
- Heavy duty chambered construction with space for air for additional insulation.
- Two bulb seal gaskets between frame and glass to assure a tight seal.
- At least two non-binding cam locks to pull the sash completely closed for maximum air tightness. (Casement)
- Optional storm panel allowing for additional insulating air space, or screen for use when windows are open.
- Stainless steel, commercial strength hinge. (Casement)
- High ratio cranks that allow window to open 90 degrees for easy emergency access. (Casement)
- Dual-sealed glass units
- Glazed glass (double, triple, or Low-E) for increased energy efficiency.
- Solid wood window supports and at least 1 1/4" wood side jambs to match the thickness of your wall. (Bow / Bay Windows)
- Non-corrosive fiberglass screens with insect barrier
- Welded corners that provide a continuous air-tight frame and durable unitized strength.

